

This brochure was supplied to you by:

NEW

THE ELECTRONIC MUVI-OUTDOOR-DISPLAY



Out - and Indoor Use
(Wall bracket or Base attachment)



MUVI Communications e.K.

Managing Director: Frank Hämmerle
Knesebeckstr. 85
D-10623 Berlin

Tel. 0 30 / 341 20 46
Fax 0 30 / 341 86 27
Mail: info@muvi.de
Web: www.muvi.de

Office Husum:

Tel. 0 48 41 / 66 52 848

Commercial register no.:
HRA 61979 B Berlin-Charlottenburg
VAT no. DE 363013099

MUVI-OUTDOOR-DISPLAY THE FUNCTION



Example: Outdoor use (wall bracket)



Example: Base attachment indoors (sold separately)

The MUVI outdoor display enables a large number of new and creative applications.

Outdoors:

The MUVI outdoor display is specially designed for outdoor use and is proofed against extreme weather conditions such as storm and heavy rain. With its integrated air conditioning, the display is guaranteed to operate in a temperature range from -30 to +50 °C / -22 to +122 °F. It can also operate continuously trouble-free for 24 hours / 7 days a week. The high image quality, full HD resolution and high brightness of 1,500 cd/m² are further performance characteristics of the MUVI outdoor display.

Indoors:

The MUVI outdoor display can easily be relocated from an outdoor to an indoor location - e.g. for seasonal use - with only a few easy adjustments. A simple switchover in the software enables operation of the display in either portrait or landscape mode.

A corresponding wall bracket or special base attachment are available as optional extras.

With the assistance of the inclusive CMS content management software, the gastronomic offers can now be presented attractively and emotionally in completely new dimensions. The creativity of the design of the motifs, whether as still or animated images or as videos, are boundless.

Without additional cost, a simple to operate CMS content management software works together, and is coordinated with, the integrated media player. A number of attractive templates integrated in the content management software are available to the user at no extra cost.

Printed menus are a thing of the past!

INFORMATION AND TECHNICAL DATA

The integrated display (IP-56 certified) in its stainless steel frame has a screen diagonal of 23.8 in = 60.45 cm. With its full HD resolution (1920 x 1080 pixels) and high brightness (1,500 cd/m²), the extreme efficiency of the display is still assured in strong direct sunlight. In 24/7 continuous operating mode a service life of 50,000 hours is achievable. The integrated air conditioning guarantees efficient operation in both high summer and winter temperatures.

External measurements / Weight

Width: 68.5 cm/26.97 in Depth: 7.5 cm/2.95 in
Height: 45.5 cm/17.91 in Weight: 20 kg/44.09 lbs

Suitable for operation in all weather conditions!

- brushed stainless frame - IP-56 certified
- external frame measurements: H = 68.5 cm/26.97 in W = 45.5 cm/17.91 in D = 7.5 cm/2.95 in
- display format: screen diagonal 23.8 in = 60.45 cm
- choice of portrait or landscape format presentation
- fully functional at temperatures of -30 to +50 °C / -22 to +122 °F
- continuous operation 24 hours - 7 days a week
- high contrast rate 5,000:1 - auto-brightness sensor
- high brightness display particularly in direct sunlight (1,500 cd/m²)
- LCD technology: SV-A - image resolution 1,920 x 1,080 pixels
- anti-reflective glass / robust protective glass
- integrated media player
- complete with CMS content management software
- content update via USB-Stick/LAN (WLAN with external antenna)

Extras:

- outdoor wall bracket (removable)
- base attachment (for alternative use of the display - e.g. indoors)
- available in all normal RAL colours

